RS800 rule updates proposal February 2022

| Proposal | Section | Existing rule | New rule | Reason | |
|----------|------------|--------------------------|---|--|--|
| number | | (10 A E!) | // | | |
| 1 | Throughout | "ISAF" | "World Sailing" | ISAF changed its name to World Sailing | |
| 2 | A.4.3 | - | The RS800 class rules consist of the "RS | The link and precedence between the RS800 rules and the All Classes rules was ambiguous. | |
| | | | Class Rules: All Classes" and this | | |
| | | | document, which shall be considered as | | |
| | | | the RS800 Class Appendix to the "RS Class | | |
| | | | Rules: All Classes". If there is any conflict | | |
| | | | or inconsistency between the two | | |
| | | | documents, this document shall govern. | | |
| 3 | A.5.1 | At Class Events – see | At Class Events (being an event initiated | Clarification of what constitutes a Class Event in line with World Sailing Regulations | |
| | | RRS 86.1(c) – ISAF | and controlled by the ICA or NCA) World | | |
| | | Regulation 10.11 | Sailing Regulation 10.5(e) applies. At all | | |
| | | applies. At all other | other events RRS 87 applies. | | |
| | | events RRS 87 applies. | | | |
| 4 | C.9.2 (5) | The upper shrouds may | The upper shrouds may be formed from | Allowing split upper shrouds | |
| | | be tensioned by: a | one continuous wire with a single thimble | with separate rope purchases | |
| | | bottlescrew, or a rope | (continuous upper shrouds) or comprise | as proposed at RS800 AGM | |
| | | purchase that utilises | separate port and starboard wires (split | 2020 and agreed at RS800 | |
| | | any fittings, so long as | upper shrouds), each terminating in a | AGM 2021. | |
| | | the purchase has a | separate eye. The upper shrouds may be | | |
| | | maximum velocity ratio | tensioned by: a bottlescrew, or a rope | | |
| | | of 5:1 and is solely | purchase that utilises any fittings, so long | | |
| | | attached to the original | as the purchase has a maximum velocity | | |
| | | fitting on the mast or | ratio of 5:1 and is solely attached to the | | |
| | | mast step fitting and | original fitting on the mast or mast step | | |
| | | the upper shrouds. | fitting and the upper shrouds. Split upper | | |
| | | | shrouds may be tensioned by two | | |
| | | | separate rope purchases (one port and | | |
| | | | one starboard), each compliant with this | | |
| | | | paragraph. | | |